The **GSS-Bullet** is a SONY color CCD bullet type camera.

Standard Features
Color Camera with Sony 1/4" CCD Sensor
Employs Digital Signal Processor (DSP) IC for image control
Pixel number: NTSC = 270K / PAL = 320K. Reduced fixed pattern noise and lag. No Sticking and no image distortion
Supports functions: Auto Electronic Shutter (AES), Auto Gain Control (AGC)
White Balance (AWB), built-in Audio function (Optional)
Built-in IR-cut optional filter
Furnished with Mini Lens and Mounting Bracket
Furnished with DC power cable and video cable
DC type, low power consumption. Economical, aesthetic

Specification		
Model No.	**GSS-Bullet**	
Image Device	SONY 1/4“ Super HAD CCD sensor	
Signal System	NTSC	PAL
Effective Pixels	510(H) x 492 (V) pixels	500 (H) x 582 (V) pixels
Auto Electronic Shutter	1/60s~1/100,000s	1/50s~1/110,000s
Resolution	350 TV lines	
MIN. Illumination	0.5 LUX @ F2.0	
S/N Ratio	More than 48dB	
GAMMA	0.45	
Gain Control	Auto	
Auto White Balance	Color Temperature: 2500K~9500K	
Synchronous System	Internal, Negative sync	
Effective Range	Up to 10 Meters	
Video Output	1 Vp-p / 75 Ohms. BNC connector	
Auto Function (optional)	2 Vp-p / 50 Ohms. RCA connector. (for mode “A” only)	
Power Source	DC 12V±10%	
Power Comsumption	1.44W / 120mA	
Lens Furnished	Board lens f 3.6 mm / F2.0 (optional: f 6.0 / 8.0 / 12 mm)	
Operation Temperature	-10℃ to 50℃ (14℉ to 120℉)	